NSN 5910-00-946-6828

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-946-6828 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.400 inches **Body Length:** 1.125 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Insulation Resistance At Maximum Operating Temp:** 10.0 megohm-microfarads **Capacitance Value Per Section:** 0.330 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 2000.0 megohm-microfarads **Power Factor At Reference Tempurature In Percent:** 1.000 **Terminal Surface Treatment:** Solder **Case Insulation Material: Plastic Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life: N/a

Unit Of Measure:

NSN 5910-00-946-6828

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



_		••	• -				
1	em		ゖっ	riz	2 †1	n	
_			ıιa	114	au	VII	١.

No

Fiig:

A010b0