

View Online at https://aerobasegroup.com/nsn/5910-00-946-9299

### **Body Style:**

W/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not established

# **Terminal Length:**

1.625 inches

### **Body Diameter:**

0.432 inches

#### **Body Length:**

0.874 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Internal Electrical Connection Type:**

Extended foil

#### Features Provided:

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

25000.0 megohms

### **Capacitance Value Per Section:**

0.150 microfarads single section

# Nonderated Operating Temp:

Between -65.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

0.6000

# **Terminal Surface Treatment:**

Solder

# **Dielectric Material:**

Plastic polyethylene terephthalate

# Case Insulation Material:

Plastic

# **Test Data Document:**

81349-milc19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0