

View Online at <https://aerobasegroup.com/nsn/5910-00-948-9266>

**Body Style:**

W/thd bushing mtg, terminal (s) on one end

**Reliability Indicator:**

Not established

**Body Diameter:**

1.375 inches

**Body Length:**

2.812 inches

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Anode Type:**

Plain foil

**Impedance At Minimum Operating Temperature In Ohms:**

6.0

**Electrical Polarization:**

Polarized

**Mounting Facility Screw Thread Series Designator:**

Un

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Features Provided:**

Mounting hardware

**Capacitance Value Per Section:**

1200.000 microfarads single section

**Nonderated Operating Temp:**

Between 40.0 degrees celsius and 65.0 degrees celsius

**Thread Size:**

0.875 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

25.0 dc single section

**Tolerance Range Per Section:**

-10.00/+75.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

20.000

**Dc Leakage At Reference Temp:**

260.000 microamperes

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Data:**

81349-mil-c-62/6 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0