Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-950-5343

## Body Style:

W/thd bushing mtg, terminals on opposite ends

**Reliability Indicator:** 

Not established

# **Terminal Length:**

1.625 inches

#### **Body Diameter:**

1.000 inches

#### **Body Length:**

1.812 inches

### **Terminal Diameter:**

0.025 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

### Mounting Facility Screw Thread Series Designator:

Unef

### Mounting Facility Type And Quantity:

1 threaded bushing

#### **Features Provided:**

Hermetically sealed case

### Capacitance Value Per Section:

8.000 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Thread Size:

0.500 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

# Power Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Plastic

## **Terminal Type And Quantity:**

2 tab, solder lug



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0