Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-950-9927

## Body Style:

W/thd mtg studs, axial terminals

## **Reliability Indicator:**

Not established

### Body Diameter:

0.562 inches

## Body Length:

1.124 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

0.625 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Internal Electrical Connection Type:

Inserted tab

### Mounting Facility Screw Thread Series Designator:

Unc

### Mounting Facility Type And Quantity:

2 threaded mounting studs

#### **Features Provided:**

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

200.0 megohm-microfarads

### Capacitance Value Per Section:

0.470 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Thread Size:

0.138 inches

### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-10.00 to 10.00 percent single section

#### Case Material:

Metal

### Insulation Resistance At Reference Temp:

20000.0 megohm-microfarads

### Dissipation Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

# Case Insulation Material:

Plastic



# Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0