## NSN 5910-00-951-1491

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-951-1491
Body Style:
W/o mtg facilities, terminal (s) on one end
Reliability Indicator:
Not established
Body Diameter:
1.250 inches
Body Length:
2.500 inches
Schematic Diagram Designator:
One terminal common to each section
Anode Type:
Plain foil
Impedance At Minimum Operating Tempurature In Ohms:
1100.0
Electrical Polarization:
Polarized
Section Quantity:
3
Capacitance Value Per Section:
10.000 microfarads all sections
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
450.0 dc all sections
Tolerance Range Per Section:
-10.00/+50.00 percent 3rd section
Case Material:
Metal
Capacitive Electrode Material:
Aluminum
Dissipation Factor At Reference Tempurature In Percent:
12.0000
Dc Leakage At Reference Temp:
100.000 microamperes
Terminal Surface Treatment:
Solder
Test Data Document:

81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

4 standard tube base

Shelf Life:

N/a

## NSN 5910-00-951-1491

Electrolytic Fixed Capacitor - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A010b0