

View Online at <https://aerobasegroup.com/nsn/5910-00-951-5415>

**Body Style:**

W/o mtg facilities, terminal (s) on one end

**Reliability Indicator:**

Not established

**Body Diameter:**

1.500 inches

**Body Length:**

3.000 inches

**Schematic Diagram Designator:**

One terminal common to each section

**Anode Type:**

Plain foil

**Impedance At Minimum Operating Temperature In Ohms:**

94.0

**Electrical Polarization:**

Polarized

**Section Quantity:**

2

**Capacitance Value Per Section:**

47.000 microfarads all sections

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

350.0 dc all sections

**Tolerance Range Per Section:**

-10.00/+50.00 percent 2nd section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Dissipation Factor At Reference Temperature In Percent:**

12.0000

**Dc Leakage At Reference Temp:**

190.000 microamperes

**Terminal Surface Treatment:**

Nickel

**Test Data Document:**

81349-mil-c-62/9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 standard tube base

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0