## NSN 5910-00-952-4221

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



Body Style:  W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals  Reliability Indicator:  Not establishednot established  Terminal Length: 1.250 inches 1.250 inches  Body Diameter: 0.200 inches  Body Length: 0.400 inches  Center To Center Distance Between Terminals Parallel To Length: 0.250 inches  Terminal Diameter: 0.025 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 10.000 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic  Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a  Unit Of Measure:	View Online at https://aerobasegroup.com/nsn/5910-00-952-4221	
Reliability Indicator: Not establishednot established Terminal Length: 1.250 inches 1.250 inches Body Diameter: 0.200 inches Body Length: 0.400 inches Center To Center Distance Between Terminals Parallel To Length: 0.250 inches Terminal Diameter: 0.025 inches Terminal Diameter: 0.025 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 10.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -3.0.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Body Style:	
Not establishednot established Terminal Length:  1.250 inches 1.250 inches  Body Diameter:  0.200 inches  Body Length:  0.400 inches  Center To Center Distance Between Terminals Parallel To Length:  0.250 inches  Terminal Diameter:  0.025 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  10.000 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -0.25/+0.25 picofarads single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  0.200  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a	W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals	
Terminal Length: 1.250 inches 1.250 inches Body Diameter: 0.200 inches Body Length: 0.400 inches Center To Center Distance Between Terminals Parallel To Length: 0.250 inches Terminal Diameter: 0.025 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 10.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Reliability Indicator:	
1.250 inches 1.250 inches  Body Diameter: 0.200 inches  Body Length: 0.400 inches  Center To Center Distance Between Terminals Parallel To Length: 0.250 inches  Terminal Diameter: 0.025 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 10.000 picofarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic  Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Not establishednot established	
Body Diameter:  0.200 inches Body Length: 0.400 inches Center To Center Distance Between Terminals Parallel To Length: 0.250 inches Terminal Diameter: 0.025 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 10.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Terminal Length:	
Body Length: 0.400 inches Center To Center Distance Between Terminals Parallel To Length: 0.250 inches Terminal Diameter: 0.025 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 10.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	1.250 inches 1.250 inches	
Body Length: 0.400 inches Center To Center Distance Between Terminals Parallel To Length: 0.250 inches Terminal Diameter: 0.025 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 10.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Body Diameter:	
O.400 inches  Center To Center Distance Between Terminals Parallel To Length:  0.250 inches  Terminal Diameter:  0.025 inches  Schematic Diagram Designator:  No common or grounded electrode (s)  Capacitance Value Per Section:  10.000 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -0.25/+0.25 picofarads single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  0.200  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a	0.200 inches	
Center To Center Distance Between Terminals Parallel To Length: 0.250 inches Terminal Diameter: 0.025 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 10.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Body Length:	
Terminal Diameter:  0.025 inches Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 10.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	0.400 inches	
Terminal Diameter:  0.025 inches  Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 10.000 picofarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic  Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Center To Center Distance Between Terminals Parallel To Length:	
Schematic Diagram Designator: No common or grounded electrode (s) Capacitance Value Per Section: 10.000 picofarads single section Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	0.250 inches	
Schematic Diagram Designator: No common or grounded electrode (s)  Capacitance Value Per Section: 10.000 picofarads single section  Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Terminal Diameter:	
No common or grounded electrode (s)  Capacitance Value Per Section:  10.000 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -0.25/+0.25 picofarads single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  0.200  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a	0.025 inches	
Capacitance Value Per Section:  10.000 picofarads single section  Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:  -30.0/+30.0 single section  Tolerance Range Per Section:  -0.25/+0.25 picofarads single section  Case Material:  Plastic  Insulation Resistance At Reference Temp:  50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  0.200  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a	Schematic Diagram Designator:	
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic  Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	No common or grounded electrode (s)	
Nonderated Operating Temp:  Between -55.0 degrees celsius and 85.0 degrees celsius  Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Capacitance Value Per Section:	
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	10.000 picofarads single section	
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Nonderated Operating Temp:	
Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	Between -55.0 degrees celsius and 85.0 degrees celsius	
Nonderated Continuous Voltage Rating And Type Per Section: 500.0 dc single section  Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsiu	s:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	0.0 single section	
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Nonderated Continuous Voltage Rating And Type Per Section:	
-30.0/+30.0 single section  Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material:  Plastic  Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	500.0 dc single section	
Tolerance Range Per Section: -0.25/+0.25 picofarads single section  Case Material: Plastic Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:	
-0.25/+0.25 picofarads single section  Case Material:  Plastic  Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	-30.0/+30.0 single section	
Case Material:  Plastic Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Tolerance Range Per Section:	
Plastic Insulation Resistance At Reference Temp: 50000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	-0.25/+0.25 picofarads single section	
Insulation Resistance At Reference Temp: 50000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.200  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a	Case Material:	
Dissipation Factor At Reference Tempurature In Percent:  0.200  Terminal Type And Quantity:  2 uninsulated wire lead  Shelf Life:  N/a	Plastic	
Dissipation Factor At Reference Tempurature In Percent: 0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	·	
0.200 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a	-	
Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a		
2 uninsulated wire lead  Shelf Life: N/a		
Shelf Life: N/a		
N/a		
Unit Of Measure:		
	Unit Of Measure:	

Demilitarization:

No

## NSN 5910-00-952-4221

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0