## NSN 5910-00-952-7196

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-952-7196

**Body Style:** W/o mtg facilities, terminal (s) on one surface **Reliability Indicator:** Not established **Body Length:** 1.305 inches **Body Width:** 0.720 inches **Body Height:** 1.060 inches **Continuous Current Rating In Amps:** 8.0 **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 6.4 **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 430.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 78000.0 milliamperes Nonderated Continuous Voltage Rating And Type Per Section: 45.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Equivalent Series Resistance At Reference Tempurature In Ohms:** 0.58

. . . . . . .

Dc Leakage At Reference Temp:

10000.000 microamperes

**Terminal Type And Quantity:** 

2 tab, solder lug

## NSN 5910-00-952-7196

Electrolytic Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0