NSN 5910-00-953-5412



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-953-5412 **Body Style:** W/twist tab mtg, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** 0.078 inches **Body Diameter:** 1.000 inches **Body Length:** 2.000 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.438 inches **Terminal Diameter:** 0.063 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 13.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 275.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 75.0 dc single section **Tolerance Range Per Section:** -10.00/+125.00 percent single section Case Material: Metal

Capacitive Electrode Material:

Aluminum

Dissipation Factor At Reference Tempurature In Percent:

0.1700

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

NSN 5910-00-953-5412

Electrolytic Fixed Capacitor - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0