## NSN 5910-00-954-1773

W/mtg ta (s), terminal(s) on one end

**Body Style:** 

N/a

Reliability Indicator:

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-954-1773

| Not established   |
|---|
| Terminal Length:  |
| 0.500 inches  |
| Body Diameter:  |
| 0.968 inches  |
| Body Length:  |
| 2.750 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.250 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Diameter: |
| 1.500 inches  |
| Schematic Diagram Designator:   |
| Electrod (s) grounded to case, w/gnd terminal                               |
| Anode Type:   |
| Plain foil  |
| Electrical Polarization:  |
| Polarized   |
| Mounting Facility Type And Quantity:  |
| 2 unthreaded mounting holes   |
| Features Provided:  |
| Hermetically sealed case  |
| Capacitance Value Per Section:  |
| 2000.000 microfarads single section   |
| Nonderated Operating Temp:  |
| Between -20.0 degrees celsius and 85.0 degrees celsius                      |
| Nonderated Continuous Voltage Rating And Type Per Section:                  |
| 30.0 dc single section  |
| Tolerance Range Per Section:  |
| -10.00/+75.00 percent single section  |
| Case Material:  |
| Metal   |
| Capacitive Electrode Material:  |
| Aluminum  |
| Terminal Surface Treatment:   |
| Solder  |
| Terminal Type And Quantity:   |
| 2 tab, solder lug   |
| 2 lab, soluel lug   |

## NSN 5910-00-954-1773

Electrolytic Fixed Capacitor - Page 2 of 2



| U | n | it | Of | Μe | eas | ur | e: |
|---|---|----|----|----|-----|----|----|
|   |   |    |    |    |     |    |    |

--

Demilitarization:

No

Fiig:

A010b0