## NSN 5910-00-954-3004

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-954-3004

Body Style:
W/thd bushing mtg, terminal (s) on one end
Reliability Indicator:
Not established
Terminal Length:
3.000 inches
Body Diameter:
1.000 inches
Body Length:
2.625 inches
Center To Center Distance Between Terminals Parallel To Length:
0.141 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unef
Mounting Facility Type And Quantity:
1 threaded bushing
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
3.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.500 inches
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Metal

**Insulation Resistance At Reference Temp:** 

2000.0 megohm-microfarads

**Power Factor At Reference Tempurature In Percent:** 

1.0000

**Terminal Surface Treatment:** 

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-00-954-3004

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Sneit Lite:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A010b0