

View Online at https://aerobasegroup.com/nsn/5910-00-954-6246

## **Body Style:**

W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surface

### **Reliability Indicator:**

Not establishednot establishednot established

### **Terminal Length:**

1.250 inches 1.250 inches 1.250 inches

### **Body Length:**

0.190 inches

#### **Body Width:**

0.190 inches

### **Body Height:**

0.090 inches

## Center To Center Distance Between Terminals Parallel To Length:

Between 0.185 inches and 0.215 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### **Capacitance Value Per Section:**

180.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-66.0/+22.0 with rated voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 150.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

### **Case Material:**

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

### **Power Factor At Reference Tempurature In Percent:**

2.500

## **Terminal Surface Treatment:**

Solder

## Test Data Document:

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

## **Specification Data:**

81349-mil-c-11015/18 government specification

# Shelf Life:

N/a

AeroBase Group

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0