## NSN 5910-00-956-3117

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-956-3117
Body Style:
W/o mtg facilities, axial terminals
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Diameter:
0.400 inches
Body Length:
1.563 inches
Terminal Diameter:
Between 0.020 inches and 0.034 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Internal Electrical Connection Type:
Extended foil
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
40000.0 megohms
Capacitance Value Per Section:
100.000 nanofarads single section
Nonderated Operating Temp:
Between -65.0 degrees celsius and 65.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-170.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Tolerance Range Per Section:
-5.00/+5.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
100000.0 megohms
Dissipation Factor At Reference Tempurature In Percent:
0.1000
Terminal Surface Treatment:
Solder
Dielectric Material:

Plastic polystyrene

NSN 5910-00-956-3117
Plastic Dielectric Fixed Capacitor - Page 2 of 2



Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Reference Number Differentiating Characteristics:
Navord od36190
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A010b0