

View Online at <https://aerobasegroup.com/nsn/5910-00-958-1604>

Body Style:

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

Reliability Indicator:

Not establishednot establishednot established

Terminal Length:

1.000 inches 1.000 inches 1.000 inches

Body Diameter:

0.290 inches

Body Length:

0.135 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 0.219 inches and 0.281 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Capacitance Value Per Section:

13.000 picofarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-150.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

250.0 dc single section

Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:

-30.0/+30.0 single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Ceramic

Insulation Resistance At Reference Temp:

7500.0 megohms

Quality Factor At Reference Temp:

640.0000

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Test Data Document:

01537-21d82610c drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0