NSN 5910-00-958-1727

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-958-1727

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
Between 2.000 inches and 2.500 inches
Body Length:
2.060 inches
Body Width:
1.781 inches
Body Height:
0.594 inches
Terminal Diameter:
0.040 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
11.000 microfarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
150.0 dc single section
Tolerance Range Per Section:
Tolerance Range Per Section: -5.00/+5.00 percent single section
-5.00/+5.00 percent single section
-5.00/+5.00 percent single section Case Material:
-5.00/+5.00 percent single section Case Material: Plastic
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:
-5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a

No

Fiig:

A010b0