NSN 5910-00-958-2452

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



radial terminals

View Online at https://aerobasegroup.com/nsn/5910-00-958-2452

Body Style:
W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities,
Reliability Indicator:
Not establishednot established
Terminal Length:
1.000 inches 1.000 inches
Body Diameter:
0.290 inches
Body Length:
0.162 inches
Center To Center Distance Between Terminals Parallel To Diameter:
0.250 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
2.000 picofarads single section
Nonderated Operating Temp:
Between -40.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-150.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
250.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-120.0/+120.0 single section
Tolerance Range Per Section:
-0.50/+0.50 percent single section
Case Material:
Plastic
Insulation Resistance At Reference Temp:
7500.0 megohms
Quality Factor At Reference Temp:
440.0000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5910-00-958-2452

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0