

View Online at https://aerobasegroup.com/nsn/5910-00-959-3049

## **Body Style:**

W/thd mtg hole/stud, terminal (s) on one endw/thd mtg hole/stud, terminal(s) on one endw/thd mtg hole/stud, terminal(s) on one end

## **Reliability Indicator:**

Not establishednot establishednot established

## Width Across Flats:

0.188 inches 0.188 inches 0.188 inches

## **Terminal Length:**

0.063 inches 0.063 inches 0.063 inches

### **Body Diameter:**

0.125 inches

**Body Length:** 

0.437 inches

### Schematic Diagram Designator:

Electrod (s) grounded to case

## Mounting Facility Screw Thread Series Designator:

Unc

# Mounting Facility Type And Quantity:

1 threaded mounting studs

### **Capacitance Value Per Section:**

500.000 picofarads single section

# Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-56.0/+22.0 without voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Thread Size:

0.099 inches

# Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

### Case Material:

Metal

# Power Factor At Reference Tempurature In Percent:

3.0000

# **Terminal Surface Treatment:**

Solder

# **Terminal Type And Quantity:**

1 solder stud

Shelf Life:

N/a

### Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0