

View Online at <https://aerobasegroup.com/nsn/5910-00-959-5209>

Body Style:

W/o mtg facilities, radial terminals w/o mtg facilities, radial terminals

Reliability Indicator:

Not established not established

Terminal Length:

1.500 inches

Body Diameter:

0.300 inches

Body Length:

0.156 inches

Center To Center Distance Between Terminals Parallel To Diameter:

0.250 inches

Terminal Diameter:

0.025 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

End Application:

Los angeles class ssn (688), landing craft air cushion (lcac), ticonderoga class cg (47), sturgeon class ssn (637); helicopter, advance attack, ah-1w; helicopter, carrier based asw, sh-60f; helicopter, uscg search & rescue, hh-60j; helicopter, mh-53e; helicopter, search & rescue, hh-60h

Capacitance Value Per Section:

400.000 picofarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-4.7/+4.7 without voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0