NSN 5910-00-959-5971

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-959-5971

| Body Style: | | | | | |
|-----------------------|--------------|----------------|--|--|--|
| W/mtg tabs/flanges, | terminal (s) | on one surface | | | |
| Reliability Indicator | r: | | | | |
| Not established | | | | | |
| Terminal Length: | | | | | |
| 0.750 inches | | | | | |
| Body Length: | | | | | |
| 2.060 inches | | | | | |

Body Height:

Body Width: 2.060 inches

1.190 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.970 inches and 1.150 inches

Unthreaded Mounting Hole Diameter:

Between 0.185 inches and 0.193 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.350 inches and 2.410 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Mounting Facility Type And Quantity:

2 unthreaded mounting holes

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

20.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.0000

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

NSN 5910-00-959-5971

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| ı | In | it (| Ωf | Measure: |
|---|-----|------|-----|------------|
| L | ,,, | IL ' | UI. | ivieasure. |

--

Demilitarization:

No

Fiig:

A010b0