NSN 5910-00-962-0273

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/psn/5010-00-962-0273

| View Online at https://aerobasegroup.com/nsn/5910-00-962-02/3 |
|-----------------------------------------------------------------------------------------------------------|
| Body Style: |
| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals |
| Reliability Indicator: |
| Not establishednot established |
| Terminal Length: |
| 1.500 inches 1.500 inches 1.500 inches |
| Body Diameter: |
| 1.400 inches |
| Body Length: |
| 1.250 inches |
| Terminal Diameter: |
| 0.025 inches |
| Schematic Diagram Designator: |
| No common or grounded electrode (s) |
| Capacitance Value Per Section: |
| 500.000 picofarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 30000.0 dc single section |
| Tolerance Range Per Section: |
| -20.00/+50.00 percent single section |
| Case Material: |
| Plastic |
| Insulation Resistance At Reference Temp: |
| 10000.0 megohms |
| Power Factor At Reference Tempurature In Percent: |
| 1.5000 |
| Terminal Surface Treatment: |
| Solder |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig:

A010b0