NSN 5910-00-964-1346



Plastic Dielectric Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-00-964-1346 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 1.000 inches **Body Length:** 0.650 inches **Body Width:** 0.525 inches **Body Height:** 0.225 inches Center To Center Distance Between Terminals Parallel To Length: 0.375 inches **Terminal Diameter:** Between 0.031 inches and 0.041 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Internal Electrical Connection Type:** Extended foil **Capacitance Value Per Section:** 0.100 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 50.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 50000.0 megohm-microfarads **Dissipation Factor At Reference Tempurature In Percent:** 0.5000 **Terminal Surface Treatment:** Solder **Dielectric Material:** Plastic polyethylene terephthalate **Special Features:**

Crimped leads

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-00-964-1346

Plastic Dielectric Fixed Capacitor - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0