## NSN 5910-00-964-7172

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-964-7172 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 2.000 inches **Body Diameter:** 0.250 inches **Body Length:** 0.688 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms: Electrical Polarization:** Polarized **Capacitance Value Per Section:** 5.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 25.0 dc single section **Tolerance Range Per Section:** -10.00/+75.00 percent single section Case Material: Metal **Capacitive Electrode Material:** Aluminum **Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 2.300 microamperes **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;

excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-00-964-7172

Electrolytic Fixed Capacitor - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0