

View Online at https://aerobasegroup.com/nsn/5910-00-964-7279

## **Body Style:**

W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals

## Reliability Indicator:

Not establishednot establishednot established

## **Body Diameter:**

0.225 inches

#### **Body Length:**

0.430 inches

#### **Terminal Height From Body:**

1.250 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

#### 47.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 with rated voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

20000.0 megohms

## **Dissipation Factor At Reference Tempurature In Percent:**

1.500

## **Terminal Surface Treatment:**

Solder

## **Test Data Document:**

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-11015/2 government specification

## Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# NSN 5910-00-964-7279

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

