

View Online at <https://aerobasegroup.com/nsn/5910-00-965-5345>

### Body Style:

W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals

### Reliability Indicator:

Not establishednot establishednot established

### Terminal Length:

1.250 inches 1.250 inches 1.250 inches

### Body Diameter:

0.225 inches

### Body Length:

0.540 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Capacitance Value Per Section:

12.000 picofarads single section

### Voltage Temperature Limits Per Section In Percent Capacitance Change:

-25.0/+15.0 with rated voltage applied single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

### Tolerance Range Per Section:

-10.00/+10.00 percent single section

### Insulation Resistance At Reference Temp:

20000.0 megohms

### Dissipation Factor At Reference Temperature In Percent:

1.5000

### Terminal Surface Treatment:

Solder

### Test Data Document:

81349-mil-c-11015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### Terminal Type And Quantity:

2 uninsulated wire lead

### Shelf Life:

N/a

### Unit Of Measure:

--

### Demilitarization:

No

### Fiig:

A010b0