NSN 5910-00-965-6096

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-965-6096
Body Style:
W/mtg tabs/flanges, terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
0.750 inches
Body Length:
2.000 inches
Body Width:
2.000 inches
Body Height:
1.500 inches
Center To Center Distance Between Terminals Parallel To Length:
2.375 inches
Unthreaded Mounting Hole Diameter:
0.188 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.375 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Type And Quantity:
2 unthreaded mounting holes
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
8.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

2000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

1.5000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 tab, solder lug

NSN 5910-00-965-6096

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A010b0