

View Online at <https://aerobasegroup.com/nsn/5910-00-966-8451>

| | |
|---|--|
| Body Style: | W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surface |
| Reliability Indicator: | Not establishednot establishednot established |
| Terminal Length: | 1.250 inches 1.250 inches |
| Body Length: | 0.500 inches |
| Body Width: | 0.500 inches |
| Body Height: | 0.125 inches |
| Center To Center Distance Between Terminals Parallel To Length: | 0.375 inches |
| Terminal Diameter: | 0.025 inches |
| Schematic Diagram Designator: | No common or grounded electrode (s) |
| Capacitance Value Per Section: | 0.470 microfarads single section |
| Voltage Tempurature Limits Per Section In Percent Capacitance Change: | -56.0/+22.0 without voltage applied single section |
| Nonderated Operating Temp: | Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: | 25.0 dc single section |
| Tolerance Range Per Section: | -20.00/+20.00 percent single section |
| Case Material: | Plastic |
| Insulation Resistance At Reference Temp: | 2500.0 megohm-microfarads |
| Dissipation Factor At Reference Tempurature In Percent: | 4.0000 |
| Terminal Surface Treatment: | Solder |
| Terminal Type And Quantity: | 2 uninsulated wire lead |
| Shelf Life: | N/a |
| Unit Of Measure: | -- |

Demilitarization:

No

Fiig:

A010b0