## NSN 5910-00-967-1365

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-967-1365

**Body Style:** 

W/thd mtg studs, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.670 inches

**Body Length:** 

1.624 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 

0.875 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Mounting Facility Screw Thread Series Designator:** 

Unc

**Mounting Facility Type And Quantity:** 

2 threaded mounting studs

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

40000.0 megohm-microfarads

**Capacitance Value Per Section:** 

68000.000 picofarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.138 inches

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-120.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

**Tolerance Range Per Section:** 

-2.00/+2.00 percent single section

**Case Material:** 

Metal

**Insulation Resistance At Reference Temp:** 

250000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

0.1000

NSN 5910-00-967-1365 Plastic Dielectric Fixed Capacitor - Page 2 of 2



Terminal Surface Treatment:
Solder
Case Insulation Material:
Plastic
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:

A010b0