NSN 5910-00-969-5204

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-969-5204			
Body Style:			
W/mtg tabs/flanges, terminal (s) on one surface			
Reliability Indicator:			
Not established			
Body Length:			
2.000 inches			
Body Width:			
2.000 inches			
Body Height:			
0.875 inches			
Center To Center Distance Between Terminals Parallel To Width:			
1.000 inches			
Unthreaded Mounting Hole Diameter:			
0.187 inches			
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:			
2.375 inches			
Schematic Diagram Designator:			
No common or grounded electrode (s)			
Mounting Facility Type And Quantity:			
2 unthreaded mounting holes			
Features Provided:			
Hermetically sealed case			
Insulation Resistance At Maximum Operating Temp:			
600.0 megohms			
Capacitance Value Per Section:			

2.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

12000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

1.2500

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

NSN 5910-00-969-5204

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	nit	O+	Measure:
u		v	wicasuic.

--

Demilitarization:

No

Fiig:

A010b0