## NSN 5910-00-970-0088

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-970-0088 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Body Diameter:** 1.500 inches **Body Length:** 3.061 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Plain foil **Impedance At Minimum Operating Tempurature In Ohms:** 280.0 **Electrical Polarization:** Nonpolarized **Capacitance Value Per Section:** 40.000 microfarads single section **Nonderated Operating Temp:** Between -40.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 450.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section **Case Material:** Metal **Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 200.000 microamperes **Terminal Surface Treatment:** Solder **Test Data Document:** 81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 4 standard tube base Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5910-00-970-0088

Electrolytic Fixed Capacitor - Page 2 of 2



Fiig:

A010b0