Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-970-3703

## **Body Style:**

W/mtg tabs/flanges, terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

0.625 inches

## **Body Length:**

4.000 inches

#### **Body Width:**

1.047 inches

#### **Body Height:**

## 1.938 inches

## Center To Center Distance Between Terminals Parallel To Width:

0.688 inches

## **Unthreaded Mounting Hole Diameter:**

# 0.203 inches

# Center To Center Distance Between Mounting Facilities Parallel To Height:

1.688 inches

# Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.500 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## Internal Electrical Connection Type:

Extended foil

## Mounting Facility Type And Quantity:

4 unthreaded mounting holes

## **Features Provided:**

Mounting hardware and hermetically sealed case

## Capacitance Value Per Section:

2.000 microfarads single section

## Nonderated Operating Temp:

Between -70.0 degrees celsius and 200.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

200.0 ac-rms single section and 100.0 dc single section

## **Tolerance Range Per Section:**

-2.00/+2.00 percent single section

Case Material:

Metal

## **Terminal Surface Treatment:**

Solder

**Dielectric Material:** 

Plastic polytetrafluoroethylene



# Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0