## NSN 5910-00-972-3860

Plastic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-972-3860 **Body Style:** Piston **Body Length:** Between 0.516 inches and 0.546 inches **Overall Diameter:** 0.238 inches **Quality Factor At 25 Deg Celsius:** 1000.0 **Fragility Factor:** Rugged **End Application:** Jspruance class dd (963), nimitz class cvn, virginia class cgn (41), forrestal class cv, arliegh burke class ddg, sturgeon class ssn (637), kidd class ddg, los angeles class ssn (688), ticonderoga class cg (47) **Inclosure Type:** Encapsulated **Adjustment Device Torque:** Between 1.000 inch-ounces and 8.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms **Mounting Facility Type And Quantity:** 1 clip **Nonderated Operating Temp:** Between -55.0 degrees celsius and 75.0 degrees celsius **Criticality Code Justification:** Feat Capacitance Range In Picofarads: +0.7/+3.0 single section **Nonderated Voltage Rating And Type:** 350.0 ac continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Special Features:** Weapon system essential Material: Metal base **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life:

Demilitarization: No

**Unit Of Measure:** 

N/a

## NSN 5910-00-972-3860

Plastic Dielectric Variable Capacitor - Page 2 of 2



Fiig:

A096a0