

View Online at https://aerobasegroup.com/nsn/5910-00-973-6997

#### **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

# **Terminal Length:**

1.250 inches

#### **Body Diameter:**

0.310 inches

#### **Body Length:**

1.294 inches

#### Schematic Diagram Designator:

No common or grounded electrode (s)

#### Insulation Resistance At Maximum Operating Temp:

1000.0 megohms

#### **Capacitance Value Per Section:**

180.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-750.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-120.0/+120.0 single section

#### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

50000.0 megohms

#### **Terminal Surface Treatment:**

Solder

# Test Data Document:

81349-milc20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

# Shelf Life:

N/a

## Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-00-973-6997 Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

