## NSN 5910-00-974-5641

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-974-5641 **Thread Class:** 2a **Body Style:** Piston **Overall Length:** 0.422 inches **Terminal Length:** 0.195 inches **Bushing Diameter:** Between 0.191 inches and 0.195 inches **Bushing Length:** 0.156 inches **Body Length:** 0.266 inches **Overall Diameter:** 0.266 inches **Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius:** 75.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -75.0/+75.0 single section **Quality Factor At 25 Deg Celsius:** 500.0 **Mounting Facility Screw Thread Series Designator:** Unc **Inclosure Type:** Hermetically sealed **Adjustment Device Torque:** Between 1.000 inch-ounces and 10.000 inch-ounces **Bushing Shape:** Round w/flat Insulation Dc Resistance At 25 Deg Celsius: 1000000.0 megohms **Bushing Width:** Between 0.171 inches and 0.175 inches **Mounting Facility Type And Quantity:** 1 threaded bushing **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 

0.190 inches

**Capacitance Range In Picofarads:** 

+1.0/+10.0 single section

## NSN 5910-00-974-5641

Glass Dielectric Variable Capacitor - Page 2 of 2



## Nonderated Voltage Rating And Type: 500.0 dc continuous single section Adjustment Device Drive Type And Quantity: 1 hex nut w/screwdriver slot Terminal Type And Quantity: 1 tab, solder lug Shelf Life: N/a Unit Of Measure: - Demilitarization: No

Fiig: A096a0