NSN 5910-00-977-5531

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-977-5531

Rody	Style:	
Dogv	OLVIC.	

W/o mtg facilities, terminals on opposite surfacesw/o mtg facilities on opposite surfacesw/o mtg facilities, terminals on opposite surfacesw/o mtg facilities on

Reliability Indicator:

Not establishednot established

Terminal Length:

0.875 inches

Body Length:

0.141 inches

Body Width:

0.141 inches

Body Height:

0.062 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

22.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

95.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Tolerance Range Per Section:

-2.00/+2.00 percent single section

Case Material:

Glass

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.0005

Quality Factor At Reference Temp:

5000.0000

Terminal Surface Treatment:

Silver

Terminal Type And Quantity:

2 ribbon

Shelf Life:

N/a

NSN 5910-00-977-5531

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A010b0