NSN 5910-00-978-2441

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-978-2441
Body Style:
W/o mtg facilities, radial terminalsw/o mtg facilities, radial terminalsw/o mtg facilities, radial terminals
Reliability Indicator:
Not establishednot established
Terminal Length:
1.250 inches 1.250 inches 1.250 inches
Body Diameter:
0.200 inches
Body Length:
0.400 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
3.300 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
500.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-120.0/+120.0 single section
Tolerance Range Per Section:
-0.25/+0.25 picofarads single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
10000.0 megohms
Quality Factor At Reference Temp:
400.0000
Terminal Surface Treatment:
Solder
Terminal Type And Quantity:
2 uninsulated wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Nonderated Operating Temp: Between -55.0 degrees celsius and 85.0 degrees celsius Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: 0.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 500.0 de single section Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -120.0/+120.0 single section Tolerance Range Per Section: -0.25/+0.25 picofarads single section Case Material: Metal Insulation Resistance At Reference Temp: 10000.0 megohms Quality Factor At Reference Temp: 400.0000 Terminal Surface Treatment: Solder Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life: N/a Unit Of Measure: Demilitarization:

Fiig: A010b0