## NSN 5910-00-978-9695

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-978-9695

View Online at https://aerobasegroup.com/nsn/5910-00-978-9695
Body Style:
Button type, w/o mtg tabsbutton type, w/o mtg tabsbutton type, w/o mtg tabs
Reliability Indicator:
Not establishednot established
Body Diameter:
1.875 inches
Body Length:
0.625 inches
Continuous Current Rating In Amps:
15.0
Schematic Diagram Designator:
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unc
Capacitance Value Per Section:
300.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Thread Size:
0.250 inches
0.200
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section Nonderated Continuous Voltage Rating And Type Per Section:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section  Tolerance Range Per Section:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material:  Ceramic
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Insulation Resistance At Reference Temp:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Insulation Resistance At Reference Temp: 10000.0 megohms
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.050
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:  -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section:  5000.0 dc single section  Tolerance Range Per Section:  -5.00/+5.00 percent single section  Case Material:  Ceramic  Insulation Resistance At Reference Temp:  10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent:  0.050  Terminal Surface Treatment:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section  Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section  Tolerance Range Per Section: -5.00/+5.00 percent single section  Case Material: Ceramic  Insulation Resistance At Reference Temp: 10000.0 megohms  Dissipation Factor At Reference Tempurature In Percent: 0.050  Terminal Surface Treatment: Silver
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.050 Terminal Surface Treatment: Silver Terminal Type And Quantity:
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.050 Terminal Surface Treatment: Silver Terminal Type And Quantity: 2 threaded hole
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: -750.0 single section Nonderated Continuous Voltage Rating And Type Per Section: 5000.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Ceramic Insulation Resistance At Reference Temp: 10000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.050 Terminal Surface Treatment: Silver Terminal Type And Quantity: 2 threaded hole Shelf Life:

No

Demilitarization:

## NSN 5910-00-978-9695

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0