

View Online at https://aerobasegroup.com/nsn/5910-00-978-9985

### **Body Style:**

W/o mtg facilities, axial terminals

## **Reliability Indicator:**

Not established

## **Terminal Length:**

1.625 inches

#### **Body Diameter:**

0.594 inches

#### **Body Length:**

1.688 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Features Provided:

Hermetically sealed case

### Insulation Resistance At Maximum Operating Temp:

40000.0 megohms

### **Capacitance Value Per Section:**

68000.000 picofarads single section

### Nonderated Operating Temp:

Between -65.0 degrees celsius and 65.0 degrees celsius

## Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-120.0 single section

#### Nonderated Continuous Voltage Rating And Type Per Section:

200.0 dc single section

## Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

#### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### **Case Material:**

Metal

# Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.1000

# **Terminal Surface Treatment:**

Solder

# Dielectric Material:

Plastic polystyrene

# Case Insulation Material:

Plastic

# **Test Data Document:**

81349-milc19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).



# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0