Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-980-0398

## Body Style:

W/o mtg facilities, terminal (s) on one surface

Reliability Indicator:

Not established

## Terminal Length:

1.000 inches

#### Body Length:

0.820 inches

#### Body Width:

0.300 inches

#### **Body Height:**

### 0.440 inches

### Center To Center Distance Between Terminals Parallel To Length:

0.600 inches

#### Terminal Diameter:

0.025 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

### Insulation Resistance At Maximum Operating Temp:

30.0 megohms

### Capacitance Value Per Section:

0.750 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

# Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

### Case Material:

Plastic

### Insulation Resistance At Reference Temp:

30000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

# **Terminal Surface Treatment:**

Solder

### Test Data Document:

10001-1563076 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# Terminal Type And Quantity:

2 uninsulated wire lead

### Shelf Life:

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0