NSN 5910-00-981-1613

Electrolytic Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-00-981-1613 |
|---|
| Body Style: |
| W/o mtg facilities terminal (s) on one surface |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 1.500 inches |
| Body Length: |
| 0.600 inches |
| Body Width: |
| 0.375 inches |
| Body Height: |
| 0.195 inches |
| Center To Center Distance Between Terminals Parallel To Length: |
| Between 0.190 inches and 0.210 inches |
| Schematic Diagram Designator: |
| Electrod (s) grounded to case, w/gnd terminal |
| Anode Type: |
| Solid |
| Electrical Polarization: |
| Polarized |
| Capacitance Value Per Section: |
| 18.000 microfarads single section |
| Nonderated Operating Temp: |
| Between -55.0 degrees celsius and 85.0 degrees celsius |
| Nonderated Continuous Voltage Rating And Type Per Section: |
| 50.0 dc single section |
| Tolerance Range Per Section: |
| -10.00/+10.00 percent single section |
| Case Material: |
| Plastic |
| Capacitive Electrode Material: |
| Tantalum |
| Dissipation Factor At Reference Tempurature In Percent: |
| 6.0000 |
| Terminal Surface Treatment: |
| Solder |
| Test Data Document: |
| 97983-131-88 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |

N/a

Shelf Life:

2 uninsulated wire lead

NSN 5910-00-981-1613

Electrolytic Fixed Capacitor - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A010b0