## NSN 5910-00-981-1625

Glass Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-981-1625 **Body Style:** Piston **Overall Length:** 0.901 inches **Terminal Length:** 1.500 inches **Body Length:** 0.781 inches **Overall Diameter:** 0.313 inches Tempurature Coefficient Of Capacitance Range In Ppm Per Deg Celsius: -50.0/+50.0 single section **Center To Center Distance Between Terminals Parallel To Length:** 0.625 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.281 inches **Terminal Diameter:** 0.025 inches **Quality Factor At 25 Deg Celsius:** 500.0 **Inclosure Type:** Encapsulated **Adjustment Device Torque:** Between 1.000 inch-ounces and 8.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 100.0 gigohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Capacitance Range In Picofarads: +0.8/+12.0 single section **Nonderated Voltage Rating And Type:** 750.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Terminal Type And Quantity:** 2 wire lead Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5910-00-981-1625

Glass Dielectric Variable Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A096a0