NSN 5910-00-981-4286

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-981-4286

Body Style:
W/o mtg facilities, terminal (s) on one surface
Reliability Indicator:
Not established
Body Length:
2.500 inches
Body Width:
1.188 inches
Body Height:
3.875 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.938 inches and 1.187 inches
Terminal Height From Body:
1.375 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Features Provided:
Hermetically sealed case
Capacitance Value Per Section:
10.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
400.0 dc single section
Tolerance Range Per Section:
-10.00/+10.00 percent single section
Case Material:
Metal
Dissipation Factor At Reference Tempurature In Percent:
1.0000
Terminal Surface Treatment:
Solder
Test Data Document:
81349-mil-c-18312 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 threaded stud
Specification Data:

N/a

Shelf Life:

Unit Of Measure:

81349-mil-c-18312/7 government specification

NSN 5910-00-981-4286

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0