

View Online at <https://aerobasegroup.com/nsn/5910-00-982-7357>

**Body Style:**

W/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:**

Not established/not established

**Width Across Flats:**

0.327 inches 0.327 inches

**Terminal Length:**

0.234 inches 0.234 inches

**Body Length:**

0.374 inches

**Schematic Diagram Designator:**

Feedthrough

**End Application:**

Sirius class t-afs 8; wasp class lhd; tarawa class aoe; virginia class cgn (41); spruance class dd (963); emory s.Land class cv; oliver perry class ffg; austin ship class lpd-4 amphibious transport docks

**Mounting Facility Screw Thread Series Designator:**

Unef

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Capacitance Value Per Section:**

56.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Thread Size:**

0.216 inches

**Nonderated Continuous Voltage Rating And Type Per Section:**

500.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Insulation Resistance At Reference Temp:**

100000.0 megohms

**Dissipation Factor At Reference Temperature In Percent:**

2.0000

**Terminal Surface Treatment:**

Solder

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0