

View Online at <https://aerobasegroup.com/nsn/5910-00-982-7357>

Body Style:

W/thd mtg bushing, terminals on opposite ends/w/thd mtg bushing, terminals on opposite ends

Reliability Indicator:

Not established/not established

Width Across Flats:

0.327 inches 0.327 inches

Terminal Length:

0.234 inches 0.234 inches

Body Length:

0.374 inches

Schematic Diagram Designator:

Feedthrough

End Application:

Sirius class t-afs 8; wasp class lhd; tarawa class aoe; virginia class cgn (41); spruance class dd (963); emory s.Land class cv; oliver perry class ffg; austin ship class lpd-4 amphibious transport docks

Mounting Facility Screw Thread Series Designator:

Unef

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

56.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.216 inches

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

2.0000

Terminal Surface Treatment:

Solder

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0