

View Online at <https://aerobasegroup.com/nsn/5910-00-983-6241>

**Reliability Indicator:**

Established

**Continuous Current Rating In Amps:**

2.3

**Schematic Diagram Designator:**

No common or grounded electrode (s)

**Capacitance Value Per Section:**

18.000 picofarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 120.0 degrees celsius

**Temperature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:**

0.0 single section

**Nonderated Continuous Voltage Rating And Type Per Section:**

3000.0 dc single section

**Tolerance Of Temperature Coefficient Per Section In Ppm Per Deg Celsius:**

-30.0/+30.0 single section

**Tolerance Range Per Section:**

-5.00/+5.00 percent single section

**Case Material:**

Ceramic

**Insulation Resistance At Reference Temp:**

5000.0 megohms

**Terminal Surface Treatment:**

Solder

**Test Data Document:**

80045-1501-20 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0