NSN 5910-00-984-3595

Body Style:

W/thd mtg studs, axial terminals

Reliability Indicator:

Not established

Terminal Length:

0.296 inchesBody Diameter:1.000 inchesBody Length:2.375 inches

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-984-3595

1.375 inches Schematic Diagram Designator:
Schematic Diagram Designator:
Continued Diagram Designator.
No common or grounded electrode (s)
Mounting Facility Screw Thread Series Designator:
Unc
Mounting Facility Type And Quantity:
2 threaded mounting studs
Features Provided:
Hermetically sealed case
Insulation Resistance At Maximum Operating Temp:
10.0 megohm-microfarads
Capacitance Value Per Section:
0.470 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Thread Size:
0.138 inches
Nonderated Continuous Voltage Rating And Type Per Section:
1000.0 dc single section
Tolerance Range Per Section:
-10.00 to 10.00 percent single section
Case Material:
Metal
Insulation Resistance At Reference Temp:
Insulation Resistance At Reference Temp:
Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads
Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment:
Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000
Insulation Resistance At Reference Temp: 20000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Surface Treatment:

NSN 5910-00-984-3595

Paper Dielectric Fixed Capacitor - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0