

View Online at <https://aerobasegroup.com/nsn/5910-00-984-3899>

**Body Style:**  
W/o mtg facilities terminal (s) on one surfacew/o mtg facilities terminal(s) on one surfacew/o mtg facilities terminal(s) on one surface

**Reliability Indicator:**  
Establishedestablishedestablished

**Reliability Failure Rate Level In Percent:**  
1.00001.00001.0000

**Terminal Length:**  
1.250 inches

**Body Length:**  
0.190 inches

**Body Width:**  
0.190 inches

**Body Height:**  
0.090 inches

**Center To Center Distance Between Terminals Parallel To Length:**  
0.200 inches

**Terminal Diameter:**  
0.025 inches

**Schematic Diagram Designator:**  
No common or grounded electrode (s)

**Insulation Resistance At Maximum Operating Temp:**  
10000.0 megohms

**Capacitance Value Per Section:**  
2700.000 picofarads single section

**Voltage Tempurature Limits Per Section In Percent Capacitance Change:**  
-25.0/+15.0 with rated voltage applied single section

**Nonderated Operating Temp:**  
Between -55.0 degrees celsius and 125.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**  
100.0 dc single section

**Tolerance Range Per Section:**  
-10.00/+10.00 percent single section

**Case Material:**  
Plastic

**Insulation Resistance At Reference Temp:**  
100000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:**  
2.5000

**Terminal Surface Treatment:**  
Solder

**Test Data Document:**  
81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Specification Data:**

81349-mil-c-39014/1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0