NSN 5910-00-984-8678

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-984-8678

D -	٠. د	C4	٠
DU	uv	Stv	ıe:

W/thd mtg bushing, terminals on opposite endsw/thd mtg bushing endsw/thd en

Reliability Indicator:

Not establishednot established

Width Across Flats:

0.312 inches 0.312 inches 0.312 inches

Terminal Length:

1.312 inches 1.312 inches 1.312 inches

Body Length:

1.250 inches

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

. . .

Mounting Facility Type And Quantity:

1 threaded bushing

Capacitance Value Per Section:

1000.000 picofarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.250 inches

Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:

-5600.0 single section

Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:

-1000.0/+1000.0 single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5910-00-984-8678

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0