## NSN 5910-00-985-1430

Ceramic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-00-985-1430

| Body Style:   |
|---|
| W/o mtg facilities, axial terminalsw/o mtg facilities, axial terminalsw/o mtg facilities, axial terminals |
| Reliability Indicator:  |
| Not establishednot established  |
| Terminal Length:  |
| 0.250 inches 0.250 inches   |
| Body Diameter:  |
| 0.281 inches  |
| Body Length:  |
| 0.188 inches  |
| Terminal Diameter:  |
| 0.062 inches  |
| Schematic Diagram Designator:   |
| Feedthrough   |
| Capacitance Value Per Section:  |
| 15.000 picofarads single section  |
| Nonderated Operating Temp:  |
| Between -55.0 degrees celsius and 85.0 degrees celsius  |
| Nonderated Continuous Voltage Rating And Type Per Section:  |
| 500.0 dc single section   |
| Tolerance Range Per Section:  |
| -10.00/+10.00 percent single section  |
| Case Material:  |
| Metal   |
| Insulation Resistance At Reference Temp:  |
| 100000.0 megohms  |
| Power Factor At Reference Tempurature In Percent:   |
| 2.0000  |
| Quality Factor At Reference Temp:   |
| 50.0000   |
| Terminal Surface Treatment:   |
| Solder  |
| Terminal Type And Quantity:   |
| 1 tab, solder lug and 1 uninsulated wire lead   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| File:   |

A010b0