## NSN 5910-00-985-4536

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-00-985-4536

Body Style:	
W/thd mtg studs, axial terminals	
Reliability Indicator:	
Not established	
Body Diameter:	
0.400 inches	
Body Length:	
1.187 inches	
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:	
0.625 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Internal Electrical Connection Type:	
Extended foil	
Mounting Facility Screw Thread Series Designator:	
Unc	
Mounting Facility Type And Quantity:	
2 threaded mounting studs	
Features Provided:	
Hermetically sealed case	
Insulation Resistance At Maximum Operating Temp:	
200.0 megohm-microfarads	
Capacitance Value Per Section:	
0.430 microfarads single section	
Nonderated Operating Temp:	
Between -55.0 degrees celsius and 125.0 degrees celsius	
Thread Size:	
0.138 inches	
Nonderated Continuous Voltage Rating And Type Per Section:	
400.0 dc single section	
Tolerance Range Per Section:	

-5.00 to 5.00 percent single section

Case Material:

Metal

**Insulation Resistance At Reference Temp:** 

20000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

1.0000

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

## NSN 5910-00-985-4536

Paper Dielectric Fixed Capacitor - Page 2 of 2



<b>Terminal</b>	Type	And	Quantity:
-----------------	------	-----	-----------

2 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0